

# K-Tech Piston Kit Application List

Manufacture	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
Aprilia	RS250	1998	2001	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	3 clicks out (std adj)	2 - 2.5 Turns out	Remove Steel Adjuster Needle	??-???	??mm
Aprilia	RSV1000 Tuono	2002	2005	Showa	20SSK-SHO-1	20SSRK-SHO-1		3 clicks out (std adj)	2 - 2.5 Turns out	Remove Steel Adjuster Needle	??-???	120mm Spring In
Aprilia	RSV1000	2000	2008	Showa	20SSK-SHO-3	20SSRK-SHO-3		3 clicks out (std adj)	2 - 2.5 Turns out	Remove 26.50mm from std Needle.	38-288-	120mm Spring In
Aprilia	RSV1000 Factory	2004	2008	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Aprilia	RSV4 R	2009	2010	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 Turns out	Remove Steel Adjuster Needle	3838-295-	120mm Spring In
Aprilia	RSV4 R APRC	2011	2015	Sachs	118-450-030-020		125-900-509	12 clicks out			3838-295-	110mm
Aprilia	RSV4 RR	2015	2016	Showa	118-450-030-021		125-900-509	12 clicks out		Remove Steel Adjuster Needle	3838-295-	110mm
Aprilia	RSV4 Factory	2009	2010	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Aprilia	RSV4 Factory	2011	2015	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Aprilia	RSV4 RF	2015	2016	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
<b>BMW</b>	S1000RR	2010	2014	Sachs	120-012-030-020	121-012-030-020	Included in Piston Kit	12 clicks out	5 clicks out	Remove Standard Adjuster Needle	4128-205-	105mm
Ducati	748	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	748 Biposto	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	748R	1994	2003	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	37-240-	
Ducati	749	2004	2007	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	3724-300-	120mm Spring In
Ducati	749R	2004	2007	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Ducati	848	2007	2009	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	12 - 15 clicks out	Remove Steel Adjuster Needle	38-315-	150mm Spring In
Ducati	848 EVO	2010	2013	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	12 - 15 clicks out	Remove Steel Adjuster Needle	38-315-	150mm Spring In
Ducati	916	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	916 Biposto	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	916R	1999	1999	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Ducati	996	2000	2001	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	996 Biposto	2000	2001	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	996R	2000	2001	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Ducati	998	2002	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	998 Biposto	2002	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-288-	120mm Spring In
Ducati	998R	2002	2003	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Ducati	999	2004	2006	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	6 clicks out	12 - 15 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	38-300-	120mm Spring In
Ducati	999R	2004	2006	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle. Use Original Comp Assy Bolt with Hole	36-260-	
Ducati	1098	2007	2008	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SH07	12 clicks out	12 - 15 clicks out	Remove Steel Adjuster Needle	38-315-	140mm Spring In
Ducati	1098R	2007	2008	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	
Ducati	1198	2007	2008	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SH07	12 clicks out	12 - 15 clicks out	Remove Steel Adjuster Needle	38-315-	140mm Spring In
Ducati	1198R	2007	2008	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use Standard Rebound Adjuster Needle	36-260-	

# K-Tech Piston Kit Application List

Manufacture	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
Ducati	Monster 900	1997	2002	Showa	20SSK-SHO-13			6 clicks out	12 - 15 clicks out	Requires Rebound Adj Needle Machining and New Adj Rod 380 lg	???	120mm Spring In
Ducati	Monster S4	2001	2005	Showa	20SSK-SHO-13			6 clicks out	12 - 15 clicks out	Requires Rebound Aj Needle Machining and New Adj Rod 350lg	???	120mm Spring In
Ducati	ST4S	2001	2006	Showa	20SSK-SHO-13			6 clicks out	12 - 15 clicks out	Requires Rebound Adj Needle Machining and New Adj Rod	???	120mm Spring In
Ducati	1000DS Multistrada	2003	2006	Showa	20SSK-SHO-3	20SSRK-SHO-3		6 clicks out	12 - 15 clicks out	Remove Steel Adjuster Needle	???	120mm Spring In
Ducati	M1000S Monster EVO	2007	2013	Marzocchi	118-250-026-001		125-900-510	6 clicks out	12 - 15 clicks out		3822-330-	

Honda	RS125R	1997	2011	Showa	20SSK-SHO-4-12		20K-FCV-SHO-1	12 clicks out	12 - 15 clicks out	Use Standard Adjuster Rod	30-205-	95mm
Honda	NSF250R	2012>		Showa	20SSK-SHO-4-12		20K-FCV-SHO-1	12 clicks out	12 - 15 clicks out	Use Standard Adjuster Rod	30-205-	95mm
Honda	VFR400 NC30	1988	1991	Showa	20SSK-SHO-NC30				2 - 2.5 turns out	Use Piston Rod & Adj Rod Supplied		160mm
Honda	CBR600 F3	1995	1998	Showa	20SSK-SHO-7				2 - 2.5 turns out	Remove Steel Adjuster Needle	35-375-	160mm
Honda	CBR600 F4	1999	2000	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-336-	145mm
Honda	CBR600 F4i	2001	2002	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-285-	145mm
Honda	CBR600RR	2003	2004	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	4026-250-	115mm
Honda	CBR600RR	2005	2006	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	3624-270-	115mm
Honda	CBR600RR	2007	2012	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SH07	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	3624-245-	115mm
Honda	CBR900RR	1998	1999	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	4026-250-	115mm
Honda	CBR929RR	2000	2001	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3824-230-	100mm
Honda	CBR954RR	2002	2003	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3824-250-	100mm
Honda	CB1000R	2008	2017	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	3824-250-	115mm
Honda	CBR1000RR	2004	2007	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	3824-230-	100mm
Honda	CBR1000RR	2008	2011	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SH07	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	3824-235-	100mm
Honda	CBR1000L Africa Twin	2016	2019	Showa	118-500-020-016			12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	40-445-	100mm
Honda	CBR1000L Africa Twin Sport	2018	2019	Showa	118-500-020-016			12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of Needle	4126-468-	100mm
Honda	VTR1000 SP1	2000	2001	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	8 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle. Use Original Comp Assy Bolt with Hole	3824-265-	110mm
Honda	VTR1000 SP2	2002	2005	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	8 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle. Use Original Comp Assy Bolt with Hole	3824-265-	110mm
Honda	RC51	2000	2005	Showa	20SSK-SHO-3	20SSRK-SHO-3	Use Standard Adj	8 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle. Use Original Comp Assy Bolt with Hole	3824-265-	110mm
Honda	VTR1000 Firestorm	1997	2002	Showa	20SSK-SHO-7				2 - 2.5 turns out	Remove Steel Adjuster Needle	35-315-	160mm
Honda	VFR1200F	2010	2019	KYB	20SSK-KYB-10				8 - 10 Clicks Out	Shorten Adjuster Rod 1.50mm	3824-250-	150mm
Honda	VFR1200X	2010	2019	KYB	20SSK-KYB-10				8 - 10 Clicks Out	Shorten Adjuster Rod 1.50mm	3824-250-	150mm

Kawasaki	ZXR400L	1991	1999	Showa	20SSK-SHO-ZXR4				2 - 2.5 Turns Out	Use Piston Rod & Adj Rod Supplied	35-315-	115mm
Kawasaki	ZX-6R	1998	1999	KYB	20SSK-KYB-7		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	40-270-	115mm
Kawasaki	ZX-6R	2000	2002	KYB	20SSK-KYB-7		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	40-245-	115mm
Kawasaki	ZX-6R 636	2003	2004	KYB	20SSK-KYB-5		20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	36-250-	115mm
Kawasaki	ZX-6R	2003	2004	KYB	20SSK-KYB-5		20K-FCV-KYB-4	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	36-250-	115mm
Kawasaki	ZX-6R 636	2005	2006	Showa	20SSK-SHO-5-12	20SSRK-SHO-5-12	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	36-250	115mm
Kawasaki	ZX-6RR	2005	2006	Showa	20SSK-SHO-6	20SSRK-SHO-6	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	36-295-	115mm
Kawasaki	Z900	2017		KYB	118-200-020-012				2 - 2.5 turns out	Shorten Adjuster Rod 1.50mm	3624-285-	115mm
Kawasaki	Z900S	2017		KYB	118-200-020-015		125-900-514	12 clicks out	2 - 2.5 turns out	Shorten Adjuster Rod 5.00mm	3624-290-	125mm

# K-Tech Piston Kit Application List

Manufacture	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
Kawasaki	ZX-9R	1998	1999	KYB	20SSK-KYB-7		20K-FCV-KYB1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	4026-270-	115mm
Kawasaki	ZX-9R	2000	2003	KYB	20SSK-KYB-7		20K-FCV-KYB1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	4026-245-	115mm
Kawasaki	Z1000	2007	2009	Showa	20SSK-SHO-7				2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-270	115mm
Kawasaki	Z1000SX	2014	2016	Showa	118-500-020-019		20K-FCV-SHO-7	(One Leg Only)	2 - 2.5 turns out	Remove Steel Adjuster Needle ??	35-315-	115mm
Kawasaki	ZX-10R	2004	2005	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3824-240	100mm
Kawasaki	ZX-10R	2006	2007	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3824-230	100mm
Kawasaki	ZX-10R	2008	2010	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	38-235-	100mm
Kawasaki	ZRX1100	1997	2001	KYB	20SSK-KYB-1		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm		125mm
Kawasaki	ZX1400	2005	2013	KYB	20SSK-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3824-257-	95mm
Kawasaki	ZZR1400	2005	2013	KYB	20SSK-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3824-257-	95mm
Kawasaki	ZRX1100	1997	2001	KYB	20SSK-KYB-1		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	3724-330-	125mm

MV Agusta	750 F4	2003	2006	Showa	20SSK-SHO-3	20SSRK-SHO-3	20K-FCV-SHO	12 clicks out	12 - 15 clicks out	Remove Steel Adjuster Needle. Use Original Comp Assy Bolt with Hole		120mm
-----------	--------	------	------	-------	-------------	--------------	-------------	---------------	--------------------	--	--	-------

Suzuki	GSX-R600	1998	2000	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	4026-270-	115mm
Suzuki	GSX-R600	2001	2003	Showa	20SSK-SHO-1	20SSRK-SHO-2	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	4026-245-	115mm
Suzuki	GSX-R600	2004	2005	Showa	20SSK-SHO-5	20SSRK-SHO-5	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 38.70mm from tip of needle	3824-240-	100mm
Suzuki	GSX-R600	2006	2007	Showa	20SSK-SHO-5-12	20SSRK-SHO-5-12	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-270-	115mm
Suzuki	GSX-R600	2008	2010	Showa	20SSK-SHO-5-12	20SSRK-SHO-5-12	20K-FCV-SHO7	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-270-	115mm
Suzuki	GSX-R750	1997	2003	Showa	20SSK-SHO-2		20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3824-250-	110mm
Suzuki	GSX-R750	2004	2005	Showa	20SSK-SHO-5	20SSRK-SHO-5	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 38.70mm from tip of needle	3824-240-	100mm
Suzuki	GSX-R750	2006	2007	Showa	20SSK-SHO-5-12	20SSRK-SHO-5-12	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-270-	115mm
Suzuki	GSX-R750	2008	2010	Showa	20SSK-SHO-15	20SSRK-SHO-15	Included in Piston Kit	LS:13 out HS:2 1/2 turns	2 - 2.5 turns out	Remove Steel Adjuster Needle	3624-270-	115mm
Suzuki	GSX-R1000	2001	2002	KYB	20SSK-KYB-2	20SSRK-KYB-2	20K-FCV-KYB-2	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-230-	100mm
Suzuki	GSX-R1000	2003	2004	KYB	20SSK-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-2	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-230-	100mm
Suzuki	GSX-R1000	2005	2006	KYB	20SSK-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-2	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-230-	100mm
Suzuki	GSX-R1000	2007	2008	KYB	20SSK-KYB-9	20SSRK-KYB-9	Included in Piston Kit	LS:13 out HS:3 turns	8 - 10 clicks out	Use Standard Adjuster Rod	3824-240-	100mm
Suzuki	GSX-S1000	2015		KYB	118-200-020-013		20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-270-	110mm
Suzuki	TL1000S	1997	2001	KYB	120-008-230-025		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod		110mm
Suzuki	TL1000R	1998	2003	KYB	120-008-230-025		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-250-	110mm
Suzuki	GSX1300R Hayabusa	1999	2007	KYB	120-008-230-025		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-250-	100mm
Suzuki	GSX1300R Hayabusa	2008	2016	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Use Standard Adjuster Rod	3824-265-	100mm
Suzuki	GSX1300 B-King	2006	2015	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-2	12 clicks out	2 - 2.5 turns out	Shorten Adjuster Rod 1.00mm	3824-265-	100mm

# K-Tech Piston Kit Application List

Manufacture	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
Triumph	Daytona 600	2002	2004	KYB	20SSK-KYB-4		20K-FCV-KYB-1A	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3624-245-	115mm
Triumph	Daytona 675	2006	2008	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3624-245-	115mm
Triumph	Daytona 676	2009	2012	KYB	20SSK-KYB-9	20SSRK-KYB-9	Included in Piston Kit	LS:13 out HS:3 turns	8 - 10 clicks out	Use Standard Adjuster Rod	3624-235-	115mm
Triumph	Street Triple 675R	2008	2012	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3624-245-	115mm
Triumph	Daytona T509	1997	1998	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 26.50mm from tip of needle	4026-245-	110mm
Triumph	Daytona T595	1997	1998	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 26.50mm from tip of needle	4026-245-	110mm
Triumph	Daytona 955I	1997	2006	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 26.50mm from tip of needle	4026-245-	110mm
Triumph	Speed Triple 1050	2005	2010	Showa	20SSK-SHO-11		N/A	1.5 turns out	1.5 turns out	Remove 24.00mm from tip of needle	38-288-	150mm Spring In
Triumph	Speed Triple 1050	2011	2015	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SH-07	12 clicks out	2 - 2.5 turns out	Remove 24.00mm from tip of needle	38-288-	150mm Spring In
Triumph	Speed Triple 1050S	2011	2015	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SH-07	12 clicks out	2 - 2.5 turns out	Remove 24.00mm from tip of needle		
Triumph	Tiger 1050	2007	2011	Showa	20SSK-SHO-9		N/A	1.5 turns out	1.5 turns out	Remove 24.00mm from tip of needle	38-288-	100mm Spring In

Yamaha	YZF-R6	1998	2000	KYB	20SSK-KYB-4		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20mm	3624-250-	145mm
Yamaha	YZF-R6	2001	2002	KYB	20SSK-KYB-4		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20mm	37-240-	145mm
Yamaha	YZF-R6	2003	2004	KYB	20SSK-KYB-4		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20mm	37-240-	145mm
Yamaha	YZF-R6	2005	2005	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3624-245-	115mm
Yamaha	YZF-R6	2006	2007	Soqi	20SSK-KYB-4-HL	20SSRK-KYB-4-HL	Included in Piston Kit	LS:10 out HS:2.5 turns	10 - 14 clicks out	Remove Standard Nut from Piston Rod	3624-245-	115mm
Yamaha	YZF-R6	2008	2015	Soqi	20SSK-KYB-4-HL	20SSRK-KYB-4-HL	Included in Piston Kit	LS:10 out HS:2.5 turns	24 - 30 clicks out	Remove Standard Nut from Piston Rod	3624-250-	115mm
Yamaha	YZF-R6	2016	2016	KYB	20SSK-KYB-9	20SSRK-KYB-9	Included in Piston Kit	LS:13 out HS:3 turns	8 - 10 clicks out	Shorten Adjuster Rod 1.50mm	3624-270-	115mm
Yamaha	YZF-750R	1993	1994	KYB	20SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	36-336	110mm
Yamaha	FZ-09	2014	2016	KYB	118-200-020-012					Shorten Adjuster Rod 1.50mm	3624-300-	140mm
Yamaha	FZ-09	2017		KYB	118-200-020-014					Shorten Adjuster Rod 1.50mm	3624-300-	140mm
Yamaha	MT-09	2014	2016	KYB	118-200-020-012					Shorten Adjuster Rod 1.50mm	3624-300-	140mm
Yamaha	MT-09	2017		KYB	118-200-020-014					Shorten Adjuster Rod 1.50mm	3624-300-	140mm
Yamaha	MT-09 SP	2018		KYB	20SSK-KYB-9	20SSRK-KYB-9	Included in Piston Kit	LS:13 out HS:3 turns	8 - 10 clicks out	Use Standard Adjuster Rod	3624-305-	160mm
Yamaha	YZF-R1	1998	2001	KYB	20SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	36-250	110mm
Yamaha	YZF-R1	2002	2003	KYB	20SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten Adjuster Rod 20.00mm	38-250	100mm
Yamaha	YZF-R1	2004	2006	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	16-20 clicks out	Shorten Adjuster Rod 20.00mm	38-230	100mm
Yamaha	YZF-R1	2007	2008	KYB	24SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-3	12 clicks out	16-20 clicks out	Use Standard Adjuster Rod	38-230	100mm
Yamaha	FZS1000 FAZER	2000	2005	Soqi	20SSK-KYB-8		Use Standard Adj	8-10 clicks out	20-24 clicks out	Shorten Adjuster Rod 20.00mm	36-336	130mm
Yamaha	FZ1	2006	2015	Soqi	115-200-020-011			14-16 Clicks Out	18-20 Clicks Out	Shorten Adjuster Rod 4.50mm	36-336	115mm
Yamaha	FJR1300	2004	2007	Soqi	20SSK-KYB-8		Use Standard Adj	8-10 clicks out	20-24 clicks out	Shorten Adjuster Rod 20.00mm	4126-260-	105mm